


Suzhou Newlead Augmented Intelligence Equipment Co.Ltd

D750 Flat Wire Drawing machine

(Specially designed drawing machines for producing precise sized flat wires)



1. Construction characteristics

(1) Power control: The motor is controlled by a variable frequency drive with continuous speed regulation, which can be adjusted freely within 75-180 meters per minute. The touch screen displays the current speed of the host. The motor is equipped with a separate frequency converter, and the signal of the change in resistance value is automatically calculated under the control of the PLC through a pneumatic rod ruler. The frequency converter is commanded to immediately adjust the motor speed, keep the tension rod stable, and adjust the optimal tension.

- (2) Wire laying method: 800 shaftless rotary arm wire laying.
- (3) Drawing method: spray+immersion mode.
- (4) Wire tension triangle pneumatic tension.
- (5) Wire collection method: 800 axis dynamic gantry precision sorting.
- (6) Transmission method: The entire machine is driven by couplings and high tension belts.



Suzhou Newlead Augmented Intelligence Equipment Co.Ltd

(7) Using special high-quality products:

The A reducer adopts a square box hard tooth surface reducer.

B bearings are all imported or national first-class brand bearings.

(8) Inching device:Place a foot switch, and when threading, the operator can easily move the foot switch to make the machine run at low speed (about 10m/min). When abnormal situations such as disorderly wiring occur during production operation, this switch can be pressed to emergency stop the machine.

2. Performance parameters:

- (1) Entry range: 3-12.5mm wide, 1.0-3.8mm thick flat wire
- (2) Mechanical speed: 180 meters/minute/Max. (production speed is determined according to different specifications).
- (3) Drawing range: less than 25% reduction in surface area
- (4) Flat drawing dies: 1
- (5) Flat Puller Outer Diameter: 750mm, Drawing Oil Concentration 15%, PH 8.0-9.5, Conductivity 2000 (6) Mold outer diameter: Flat wire 50MM (25-40 wide).
- (7) Flat wire drawing motor: 15HP reducer AC motor and 15HP tension type frequency converter
- (8) Wire collection motor: 10HP reducer AC motor and 10HP tension type frequency converter
- (9) Cable laying servo motor A: 3KW+PLC
- (10) Roll up capacity: 1000 KG/MAX, (spool 800 * 400 * 450 or as specified by the customer)
- (11) Brake: Pneumatic disc brake
- 3. Composition of the machine:
- (1) Magnetic powder tension shaftless arm type pay off machine: 1 unit
- (2) 750 drawing machine: 1 set



Suzhou Newlead Augmented Intelligence Equipment Co.Ltd

(3) Washing machine: 1 set

(4) Triangle tension frame: 1 set

(5) 1000KG axial winding machine: 1 set

(6) Single pull machine water tank: 1 set

(7) Washing machine water tank: 1 set

(8) Electric control system: 1 set